

Appendix 2

This document printed 30 May 2023. Made using Mathematica v.13.0

2.1 Starting Assumptions

```
In[*]:= $Assumptions = (
  disp > 0 && (*Dispersal rate*)
  w > 0 && (*EPC width*)
  r0 > 0 && (*Maximum growth rate (at optima)*)
  v > 0 &&
  (*Speed of climate change --- we fix the sign of v but keep that of a open*)
  Element[y, Reals] && (*Spatial dimension, moving reference frame*)
  Element[a, Reals] && (*Asymmetry of Morse EPC*)
  frontWidth > 0 && (* Property of population density shape,
  used to work around some Sqrt[] expressions. *)
  sigma > 0 (*standard deviation of high-frequency environmental variation*)
)
```

```
Out[*]=
disp > 0 && w > 0 && r0 > 0 && v > 0 && y ∈ ℝ && a ∈ ℝ && frontWidth > 0 && sigma > 0
```

```
In[*]:= (* Various rules used to simplify expressions later *)
```

```
dispRule = Solve[frontWidth ==  $\frac{\sqrt{\text{disp}}}{\sqrt{r0}}$ , disp] // Last
```

```
frontWidthRule = Solve[frontWidth ==  $\frac{\sqrt{\text{disp}}}{\sqrt{r0}}$ , frontWidth] // Last
```

```
r0Rule = Solve[frontWidth ==  $\frac{\sqrt{\text{disp}}}{\sqrt{r0}}$ , r0] // Last
```

```
Out[*]=
{disp → frontWidth2 r0}
```

```
Out[*]=
{frontWidth →  $\sqrt{\frac{\text{disp}}{r0}}$ }
```

```
Out[*]=
{r0 →  $\frac{\text{disp}}{\text{frontWidth}^2}$ }
```

2.2 Defining Core Functions

Start by writing down the basic equation, without the non-linearity, in the co-moving reference frame. Here $g()$ is the EPC, $f()$ is population density (called $u_{\text{inv}}()$ in the paper), and lam is the overall growth rate (λ).

```
In[*]:= eq = lam * f[y] == g[y] * f[y] + v f'[y] + disp f''[y];
eq // TraditionalForm
```

```
Out[*]//TraditionalForm=
lam f(y) = disp f''(y) + v f'(y) + f(y) g(y)
```

2.2.1 Morse (Asymmetric) EPC

```
In[*]:= (* Define Morse Potential Function *)
gMorseRule = {g → Function[y, r0 (1 - 1 / (a^2 w^2) (1 - Exp[a y])^2)]}
(* Solve differential equation for f in terms of y.
   Rather than first computing ψ() and from this f() (u_inv() in the paper),
   we here compute f() directly and let Mathematica to all the housekeeping.
   NB: The solution is very complex, so not showing here! *)
morseSol = DSolve[eq /. gMorseRule, f, y] // Last;
```

```
Out[*]=
{g → Function[y, r0 (1 - (1 - Exp[a y])^2 / (a^2 w^2)))]}
```

```
In[*]:= (* Add additional condition for localisation of climatic niche
   (otherwise don't get positive growth anywhere and it blows up)*)
```

```
In[*]:= (* Negativity of g() in the tails leads to additional conditions,
   but we don't make them explicit in order not to confuse Mathematica.*)
Reduce[$Assumptions && 1 / (a^2 w^2) > 1, a]
```

```
Out[*]=
y ∈ ℝ && w > 0 && v > 0 && sigma > 0 && r0 > 0 &&
frontWidth > 0 && disp > 0 && ( - 1/w < a < 0 || 0 < a < 1/w )
```

```
(* The the solution we are looking for is that containing the
   Laguerre polynomial of zeroth order. Hence, we extract the order of the
   Laguerre polynomial and isolate the condition for it to be zero. *)
morseCond = 0 == (Cases[f[y] /. morseSol, LaguerreL[n_, _, _] → n, Infinity, 1] // First)
```

```
Out[*]=
0 == 1 / (2 a^2 disp w) ( 2 sqrt[disp r0] - a^2 disp w - sqrt[4 disp r0 + 4 a^2 disp lam w^2 - 4 a^2 disp r0 w^2 + a^2 v^2 w^2] )
```

2.2.2 Harmonic EPC

```
In[*]:= (*Also consider the harmonic EPC. Needed below for baseline calculations of shift*)
(*Follows same logic.*)
gHarmRule = {g → Function [y, r0 (1 - y^2 / (w^2))]} (* Harmonic Potential *)
harmSol = DSolve[eq /. gHarmRule, f, y] // Last;
harmCond = 0 == (Cases[f[y] /. harmSol, HermiteH[n_, _] → n, Infinity, 1] // First);
harmLamRule = Solve[harmCond, lam] // Last // FullSimplify;
(* Now compute the solution for the case
   where the Hermite polynomial is of order zero.*)
harmSolClean = {f → Function @@
  {y, f[y] /. harmSol /. harmLamRule /. dispRule /. c1 → 1 /. c2 → 0 // FullSimplify}};
```

Out[*]:=

$$\left\{g \rightarrow \text{Function}\left[y, r_0 \left(1 - \frac{y^2}{w^2}\right)\right]\right\}$$

2.3 Response 1: Population Invasion Fitness & Critical Speed of Climate Change

```
(* lambda can be derived directly from morseCond. *)
morseLamRule = Solve[morseCond, lam] // Last // FullSimplify;
Style[%, Background → LightBlue]
```

Out[*]:=

$$\left\{\text{lam} \rightarrow \frac{a^2 \text{disp}}{4} + r_0 - \frac{v^2}{4 \text{disp}} - \frac{\sqrt{\text{disp} r_0}}{w} \text{ if } \text{disp} < \frac{4 r_0}{a^4 w^2}\right\}$$

```
(* For future use, next create a neater solution, specifically for the
   case given by morseCond. Assume that the condition above is satisfied.*)
```

```
morseSolClean = {f → Function @@ {y,
  Assuming[-2 + a^2 frontWidth w < 0,

    f[y] /. morseSol /. morseLamRule /. dispRule /. c1 → 0 /. c2 → 1 // FullSimplify]
}}
```

Demonstration of Asymmetry Impact on Total Population Size

Here we work through an example of how asymmetry impacts total population size by working through Equation 4 of the main text. We compute the total population size as the integral over our approximate solution for $b(x, t)$, amongst others to demonstrate that this is *not* independent of the relative signs of v and a .

```
(* First, compute  $\psi()$  from  $f()$  ( $u_{\text{inv}}()$  in the paper). We know
that the two differ only by a factor  $\exp[v(x-vt)/(2\text{disp})]/(2D)$ ,
and are identical for  $v=0$ . So we can use this: *)
morseSolClean0 = morseSolClean /. v  $\rightarrow$  0 // FullSimplify (* generate a rule for  $\psi()$  *)
(*Test if all went well (results should be 1):*)
(Exp[-v y / (2 * disp)] f[y] /. dispRule /. morseSolClean0) /
(f[y] /. morseSolClean) // FullSimplify
```

Out[] =

$$\left\{ f \rightarrow \text{Function}\left[y, e^{-\frac{2 e^{a y} \text{frontWidth } r0 + a (-2 \text{frontWidth } r0 + a (a \text{frontWidth}^2 r0 + 0) w) y}{2 a^2 \text{frontWidth}^2 r0 w}}\right]\right\}$$

Out[] =

1

```
(* Calculate the integral in the numerator
of our formula for the scaling factor U:*)
I1 = Integrate[f[y]^2 /. morseSolClean0,
{y, -Infinity, Infinity}, GenerateConditions  $\rightarrow$  False] // FullSimplify
```

Out[] =

$$2^{1-\frac{2}{a^2 \text{frontWidth } w}} a \text{frontWidth } w (a^2 \text{frontWidth } w)^{-2+\frac{2}{a^2 \text{frontWidth } w}} \text{Gamma}\left[-1+\frac{2}{a^2 \text{frontWidth } w}\right]$$

```
(* Calculate the integral in the
denominator of our formula for the scaling factor U:*)
I2 = Integrate[Exp[-v y / (2 * disp)] f[y]^3 /. morseSolClean0 /. dispRule // Evaluate,
{y, -Infinity, Infinity}, GenerateConditions  $\rightarrow$  False] // FullSimplify
```

Out[] =

$$\frac{1}{a} 3^{\frac{1}{2}} \left(3+\frac{-6 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right) \left(\frac{1}{a^2 \text{frontWidth } w}\right)^{\frac{1}{2}} \left(3+\frac{-6 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right) \text{Gamma}\left[\frac{1}{2}\left(-3+\frac{6 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right)\right]$$

```
In[ ] := (* From this we obtain the scaling factor:*)
scalingFactorU = (lam / c) * (I1 / I2) // FullSimplify
```

Out[] =

$$\left(2^{1-\frac{2}{a^2 \text{frontWidth } w}} \times 3^{\frac{1}{2}} \left(-3+\frac{6 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right) \text{lam} \left(\frac{1}{a^2 \text{frontWidth } w}\right)^{-\frac{1}{2}-\frac{v}{2 a \text{frontWidth}^2 r0}+\frac{1}{a^2 \text{frontWidth } w}} \text{Gamma}\left[-1+\frac{2}{a^2 \text{frontWidth } w}\right]\right) / \left(c \text{Gamma}\left[\frac{1}{2}\left(-3+\frac{6 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right)\right]\right)$$

```
(* Calculate the integral over  $\exp[-v y] * (2D)^{-1} * \psi(y)$ ,
i.e. the population density for  $U=1$ :*)
I3 = Integrate[Exp[-v y / (2 * disp)] f[y] /. morseSolClean0 /. dispRule // Evaluate,
{y, -Infinity, Infinity}, GenerateConditions  $\rightarrow$  False] // FullSimplify
```

Out[] =


$$\frac{1}{a} \left(\frac{1}{\text{frontWidth } w}\right)^{\frac{1}{2}} \left(1+\frac{-2 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}\right) \text{Abs}[a]^{-1+\frac{2 \text{frontWidth } r0 - a v w}{a^2 \text{frontWidth}^2 r0 w}} \text{Gamma}\left[-\frac{1}{2}-\frac{v}{2 a \text{frontWidth}^2 r0}+\frac{1}{a^2 \text{frontWidth } w}\right]$$

```
In[*]:= (* This gives the total abundance: *)
totalAbundance = scalingFactorU * I3 // FullSimplify
```

```
Out[*]:= 
$$\left( 2^{1 - \frac{2}{a^2 \text{frontWidth} w}} \times 3^{\frac{1}{2} \left( -3 + \frac{6 \text{frontWidth} r0 - a v w}{a^2 \text{frontWidth}^2 r0 w} \right)} \text{lam Gamma} \left[ -\frac{1}{2} - \frac{v}{2 a \text{frontWidth}^2 r0} + \frac{1}{a^2 \text{frontWidth} w} \right] \right. \\ \left. \text{Gamma} \left[ -1 + \frac{2}{a^2 \text{frontWidth} w} \right] \right) / \left( a c \text{Gamma} \left[ \frac{1}{2} \left( -3 + \frac{6 \text{frontWidth} r0 - a v w}{a^2 \text{frontWidth}^2 r0 w} \right) \right] \right)$$

```

```
In[*]:= (* Now we compute λ and total abundance for a numerical example,
to illustrate that the former is symmetric in a, while the latter is not. *)
num = {a → 16 / 10, w → 1 / 2, frontWidth → 3 / 10, v → 5, r0 → 20, c → 1};
Plot[{totalAbundance, lam} /. morseLamRule /. dispRule /. v → vv /. num // Evaluate,
{vv, -10, 10}, PlotRange → {0, Automatic},
AxesLabel → {Velocity, "Total Abundance & Lambda"},
PlotLegends → {"Total Abundance", "λ"}]
```



2.3.1 Critical Speed of Climate Change

```
In[*]:= (* All we need here is lambda_0, the rest is trivial *)
lam0Rule = (lam0 → lam) /. morseLamRule /. v → 0 // FullSimplify;
Style[lam0Rule, Background → LightBlue]
```

```
Out[*]:= 
$$\text{lam0} \rightarrow \frac{a^2 \text{disp}}{4} + r0 - \frac{\sqrt{\text{disp} r0}}{w} \text{ if } \text{disp} < \frac{4 r0}{a^4 w^2}$$

```

2.3.2 Impact of Weather (high frequency variation in growth rate)

```
In[*]:= (* Convolution of Morse performance curve with Gaussian weather
variability gives another, modified Morse performance curve: *)
gMorseWeather =
  Integrate[(g[x] /. gMorseRule) * PDF[NormalDistribution[0, sigma]] [y - x],
    {x, -Infinity, Infinity}, GenerateConditions -> False]

Out[*]=
```

$$\frac{r_0 \left(-1 - e^{2a(a\sigma^2 + y)} + 2e^{\frac{a^2\sigma^2}{2} + ay} + a^2 w^2 \right)}{a^2 w^2}$$

2.3.3 How effective values of key parameters are impacted by weather

```
(* We compute the effective Morse performance curve
parameters that result for a Morse performance curve under the
influence of weather. Because doing it directly takes too long,
so we do it only for the first three terms of a series expansion of g[y]:*)
gWSol1 =
  Solve[And@@Table[SeriesCoefficient[
    Series[(g[y] /. gMorseRule /. {r0 -> r02, w -> w2, y -> y - y2}) - gMorseWeather,
      {y, 0, 2}],
    n] == 0,
    {n, 1, 1}],
    {r02}] // FullSimplify // Last;

gWSol2 = Assuming[Element[y2, Reals],
  Solve[And@@Table[SeriesCoefficient[
    Series[(g[y] /. gMorseRule /. {r0 -> r02, w -> w2, y -> y - y2}) - gMorseWeather,
      {y, 0, 2}],
    n] == 0,
    {n, 2, 2}] /. gWSol1, {y2}]] // Last;

gWSol3 = Assuming[Element[y2, Reals] && w2 > 0 && a > 0,
  Solve[And@@Table[SeriesCoefficient[Series[
    (g[y] /. gMorseRule /. {r0 -> r02, w -> w2, y -> y - y2}) - gMorseWeather,
      {y, 0, 2}],
    n] == 0,
    {n, 0, 0}] /. gWSol1 /. gWSol2 /. w2 -> Sqrt[w4] // FullSimplify,
    {w4}]] // Last // FullSimplify;
```

```
In[*]:= morseWeatherRule =
  Assuming[a > 0 (* This is just not to confuse Mathematica *), {r0 → r02,
    frontWidth → Sqrt[r0 / r02] * frontWidth,
    y → y - y2,
    w → Abs[w2]
  } /. gWSol1 /. gWSol2 /. w2 → Sqrt[w4] /. gWSol3 // FullSimplify]
```

Out[*]=

$$\left\{ r0 \rightarrow \frac{r0 \left(-1 + e^{-a^2 \sigma^2} + a^2 w^2 \right)}{a^2 w^2}, \text{frontWidth} \rightarrow a e^{\frac{a^2 \sigma^2}{2}} \text{frontWidth} w \sqrt{\frac{1}{1 + e^{a^2 \sigma^2} \left(-1 + a^2 w^2 \right)}}, \right. \\ \left. y \rightarrow \frac{3 a \sigma^2}{2} + y, w \rightarrow \sqrt{\text{Abs} \left[\frac{1 + e^{a^2 \sigma^2} \left(-1 + a^2 w^2 \right)}{a^2} \right]} \right\}$$

```
In[*]:= (* Check consistency of calculation. Without weather variation,
we obtain the original parameters: *)
Assuming[a > 0 (* This is just not to confuse Mathematica *),
  morseWeatherRule /. sigma → 0 // FullSimplify]
```

Out[*]=

```
{r0 → r0, frontWidth → frontWidth, y → y, w → w}
```

2.3.4 How weather affects population fitness:

```
In[*]:= (* As an example, expand dependence of max local fitness up to 4th order in sigma *)
Series[r0 /. morseWeatherRule, {sigma, 0, 4}]
```

Out[*]=

$$r0 - \frac{r0 \sigma^2}{w^2} + \frac{a^2 r0 \sigma^4}{2 w^2} + O[\sigma]^5$$

```
In[*]:= (*Use above results to compute a new overall expression
for growth rate that includes the effect of weather (sigma) *)
(*For simplicity include variety of assumptions*)
morseSigWeatherRule = Assuming[a > 0,
```

```
  (Assuming[disp < \frac{4 r0}{a^4 w^2}, morseLamRule // FullSimplify] /. morseWeatherRule //
    FullSimplify)] /. Sign[1 + e^{a^2 \sigma^2} (-1 + a^2 w^2)] → 1 // FullSimplify
```

Out[*]=

$$\left\{ \text{lam} \rightarrow \frac{a^2 \text{disp}}{4} + r0 - \frac{v^2}{4 \text{disp}} - \sqrt{\frac{\text{disp} e^{-a^2 \sigma^2} r0}{w^2}} + \frac{(-1 + e^{-a^2 \sigma^2}) r0}{a^2 w^2} \right\}$$

```

In[ ]:= (* Does weather increase or decrease lambda? *)
weatherDirRule =
  D[(lam /. morseSigWeatherRule) /. sigma -> Sqrt[sigma2], {sigma2, 1}] /. sigma2 -> 0 //
  FullSimplify;
Style[weatherDirRule, Background -> LightBlue]

```

Out[]:=

$$\frac{-2 r_0 + a^2 \sqrt{\text{disp } r_0 w}}{2 w^2}$$

2.4 Response 2 - Lags

We analyze two measures of lag behind climate velocity : 1) the location of the peak density, and 2) the center of mass of the population.

2.4.1: Lag of peak

```

In[ ]:= (*Solve for location of peak of population
density in terms of y (the moving window) *)
(* Harmonic EPC, that's easy: *)
harmShift = y /. Solve[D[f[y] /. harmSolClean, y] == 0, y] // Last // FullSimplify

```

Out[]:=

$$-\frac{v w}{2 \text{ frontWidth } r_0}$$

```

In[ ]:= (*Morse EPC*)
(* Firsts, compute the position of peak under climate change,
disregarding that without climate changes is also not at zero. *)
morseShiftRaw = y /. Solve[D[f[y] /. morseSolClean, y] == 0, y] // Last // FullSimplify

```

Out[]:=

$$\frac{\text{Log}\left[1 - \frac{a (a \text{ frontWidth}^2 r_0 + v) w}{2 \text{ frontWidth } r_0}\right]}{a} \text{ if } \text{condition} \neq$$

```

In[ ]:= (* Now, compute compute actual shift and remove conditions. *)
morseShift = morseShiftRaw - (morseShiftRaw /. v -> 0) // FullSimplify // Normal

```

Out[]:=

$$\frac{-\text{Log}[\text{frontWidth } r_0] + \text{Log}\left[\frac{-2 \text{ frontWidth } r_0 + a (a \text{ frontWidth}^2 r_0 + v) w}{-2 + a^2 \text{ frontWidth } w}\right]}{a}$$

```

In[ ]:= (* To get a simpler expression, take first derivative in v at v==0,
which corresponds to the (negative of the) time lag when v is small. We
also expand to lowest non-trivial order in a to simplify further. *)
negTimeLag = Series[D[morseShift, v] /. v -> 0, {a, 0, 2}] /. frontWidthRule // FullSimplify

```

Out[]:=

$$-\frac{w}{2 \sqrt{\text{disp } r_0}} - \frac{w^2 a^2}{4 r_0} + O[a]^3$$


```

In[*]:= (* The effect of weather on the time lag: *) Assuming[ $e^{a^2 \sigma^2} (-1 + a^2 w^2) > -1$ ,
  Series[-negTimeLag /. morseWeatherRule // FullSimplify, {a, 0, 2}] //
  FullSimplify] // FullSimplify // PowerExpand // FullSimplify;
Style[%, Background → LightBlue]

```

Out[*]=

$$\frac{w}{2 \sqrt{\text{disp } r\theta}} + \frac{w \left(\sqrt{\frac{r\theta}{\text{disp}}} \sigma^2 + w \right) a^2}{4 r\theta} + O[a]^3$$

2.4.2: Centre of mass lag:

```

(* First compute the total area under the curve, to standardise with *)
morseNorm = Integrate[f[x] /. morseSolClean,
  {x, -Infinity, Infinity}, GenerateConditions → False] // FullSimplify;

(* Compute the moment generating function (using t as dummy argument of the MGF). *)
morseMGF = Integrate[Exp[t y] f[y] /. morseSolClean, {y, -Infinity, Infinity},
  GenerateConditions → False] / morseNorm // FullSimplify;

(* Compute the first moment, i.e. the centre of mass. *)
morseCentreMass = D[morseMGF, t] /. t → 0 // FullSimplify;

```

The formula for the position of the centre of mass looks singular for $v, a \rightarrow 0$, but actually it's smooth (technically, it can be “analytically continued” to $a \rightarrow 0$ and $v \rightarrow 0$). Based on the symmetry of the problem, centre of mass (in the co-moving reference system) is given by

$\text{centre of mass} = c_1 a + c_2 v + c_3 a^3 + c_4 a^2 v + c_5 a v^2 + c_6 v^3 + \text{terms of order 5 and higher, with some constants } c_1, \dots, c_6.$

However, here we are only interested in the lag in time for small v . This can be computed as $D[\text{centre of mass}, v] \text{ (at } v=0) = c_2 + c_4 a^2 + \text{terms of order 4 and higher}$. Since c_2 is the same as for the harmonic potential, we take it from there.

To get c_4 , we first compute $(1/2) * d^2(\text{centre of mass}) / da^2 = 3 c_3 a + c_4 v + \text{terms of order 2 and higher}$ (and calls this “morseCentreMassEffect”), then takes the limit $a \rightarrow 0$ (which remove the c_3 term and all higher order terms containing a) and then takes the derivative with respect to v at $v = 0$ (which converts $c_4 v$ to c_4 and drops the remaining higher order terms). The result is c_4 .

Finally, the lag $c_2 + c_4 a^2$ is assembled from the isolated terms.


```

In[*]:=
morseCentreMassEffect = (1/2) D[morseCentreMass, {a, 2}] // FullSimplify;
morseCentreMassCorrection =
  a^2 D[Limit[morseCentreMassEffect, a → 0, Direction → "FromAbove"] // FullSimplify,
    v] /. v → 0
harmNegLag = D[y /. Solve[D[f[y] /. harmSolClean, y] == 0, y] // Last, v];

morseCentreMassNegLag = harmNegLag + morseCentreMassCorrection // FullSimplify;

(*Present in a neater form*)
morseCentreMassNegLag /. frontWidthRule // FullSimplify // PowerExpand //
  FullSimplify // Apart // PowerExpand

```

 **Limit:** Warning: Assumptions that involve the limit variable are ignored.

Out[*]=

$$-\frac{a^2 w^2}{2 r_0}$$

Out[*]=

$$-\frac{w}{2 \sqrt{\text{disp}} \sqrt{r_0}} - \frac{a^2 w^2}{2 r_0}$$

```

In[*]:= (* Now include the effect of weather variation as for the peak lag above. *)
Assuming[Exp[a^2 sigma^2 (-1 + a^2 w^2)] > -1 && a > 0,
  Series[-morseCentreMassNegLag /. morseWeatherRule /. frontWidthRule // FullSimplify,
    {a, 0, 2}] // FullSimplify // FullSimplify // PowerExpand // FullSimplify];
Style[%, Background → LightBlue]

```

Out[*]=

$$\frac{w}{2 \sqrt{\text{disp}} r_0} + \frac{w (\sqrt{\text{disp}} r_0 \sigma^2 + 2 \text{disp} w) a^2}{4 \text{disp} r_0} + O[a]^3$$

2.5 Response 3: Local of Maximum Sensitivity

```

In[*]:= (* Calculation of location (in terms of y) of maximum sensitivity *)
sensitivity =
  (f[y] /. morseSolClean /. v → -v) * (f[y] /. morseSolClean) // FullSimplify;
ySenseRule = Solve[D[sensitivity, y] == 0, y] // FullSimplify // Last;

Style[ySenseRule, Background → LightBlue]

```

Out[*]=

$$\left\{ y \rightarrow \frac{\text{Log}\left[1 - \frac{1}{2} a^2 \text{frontWidth} w\right]}{a} \text{ if } w < \frac{2}{a^2 \text{frontWidth}} \right\}$$

```
In[*]:= (*Calculate f at y=0, to standardise plotting height*)
f0 = f[y] /. morseSolClean /. y -> 0
```

```
Out[*]:=
```

$$\frac{1}{e^{-\frac{1}{a^2 \text{frontWidth } w}}}$$


```
In[*]:= num = {a -> 16 / 10, w -> 1 / 2, frontWidth -> 3 / 10, v -> 5, r0 -> 20, c -> 1};
(lam0 - v^2 / (4 * disp)) /. lam0Rule /. dispRule /. num
(* check if invasion growth rate positive *)
Plot[{g[y] 0.5 /. gMorseRule, (* Plot out Growth function [Blue] *)
      f[y] * amplitudeFactorU /. morseLamRule /. dispRule /. morseSolClean,
      (* Plot out psi function, standardised to equal 1 at y=0 [Orange] *)
      sensitivity * 1000} /. (* Plot out Sensitivity, also scaled [Green] *)
      num // Evaluate, {y, -4, 1}, (* Define conditions to plot *)
      PlotRange -> {-6, All}, (* vertical axis range *)
      PlotLabel -> "a = 1.6",
      PlotLegends -> Placed[LineLegend[ColorData[97, "ColorList"][[1 ;; 3]],
        {"EPC x 0.5", "Density", "Sensitivity x 1000"}], {0.25, 0.8}]]
```

```
Plot[{g[y] 0.5 /. gMorseRule, (* Plot out Growth function [Blue] *)
      f[y] * amplitudeFactorU /. morseLamRule /. dispRule /. morseSolClean,
      (* Plot out psi function, standardised to equal 1 at y=0 [Orange] *)
      sensitivity * 1000} /. a -> -a /.
      (* Plot out Sensitivity, also scaled [Green] *)
      num // Evaluate, {y, -2, 3}, (* Define conditions to plot *)
      PlotRange -> {-6, All}, (* vertical axis range *)
      PlotLabel -> "a = -1.6",
      PlotLegends -> Placed[LineLegend[ColorData[97, "ColorList"][[1 ;; 3]],
        {"EPC x 0.5", "Density", "Sensitivity x 1000"}], {0.8, 0.8}]]
```


```
Out[*]:=
```

```
25 559
-----
4500
```

```
Out[*]:=
```



Out[]=




```
In[ ]:= Plot[y /. ySenseRule /. frontWidth → 1 /. w → 1 // Evaluate,
  {a, -2, 2}, AxesLabel → {"Asymmetry", "Location of Peak Sensitivity"},
```

```
PlotLabel → "Location of Peak Sensitivity in terms of asymmetry\nPeak sensitivity
  depends on shape of curve, not on \n direction of climate change" ]
```

Out[]=

Location of Peak Sensitivity in terms of asymmetry
 Peak sensitivity depends on shape of curve, not on
 direction of climate change
 Location of Peak Sensitivity



2.6 Example Plots

```


In[*]:= num = Join[dispRule, {w → 1, r0 → 1, a → 3 / 4, v → 0.5, frontWidth → 0.6}];
morseLamRule /. num
(*Repeatedly put in the parameters to find what lambda is with these*)
Plot[g[y] /. gMorseRule /. num, {y, -7, 7},
      PlotRange → {-r0, r0} /. num // Evaluate,
      PlotLabel → "Shape of EPC"]
Plot[f[y] / Abs[morseNorm] /. morseSolClean /. num // Evaluate, {y, -7, 7},
      PlotRange → All,
      PlotLabel → "Shape of population density"]

```


Out[*]=

{lam → 0.277014}

Out[*]=



Out[*]=



```

In[*]:= (* Evaluation through time*)
(* Specify movement equation explicitly,
then put into moving reference frame. Climate change starts at t=0. *)

```

```

In[ ]:= eqPLOT = (D[f[x - x0[t], t], t] == disp * D[f[x - x0[t], t], {x, 2}] +
    g[x - x0[t]] * f[x - x0[t], t] - f[x - x0[t], t]^2) /. x -> y + x0[t];
L = 13; (* 0.5 * spatial extent *)
tMin = -20;
tMax = 25;
num =
    Join[gMorseRule,
        {disp -> 0.2,
         v0 -> 0.45, (*rate of climate change*)
         a -> 0.9,
         w -> 1,
         r0 -> 1,   x0 -> Function[t, t * v0 * HeavisideTheta[t]] }];

sol = NDSolve[eqPLOT &&
    f[y, tMin] == (11 * f[y] /. morseSolClean /. v -> 0 /. frontWidthRule) &&
    (*Set starting distribution to 0.2*(1-(1-Exp[y])^2) *)
    f[-L, t] == 0 &&
    f[L, t] == 0 /. num // FullSimplify,
    f, (*Solve for f*)
    {y, -L, L}, (*Range of y to consider*)
    {t, tMin, tMax} (*Range of times to consider*)
] // Last

```

Out[]:=

```

{f -> InterpolatingFunction[
    {
        
        Domain: {{-13., 13.}, {-20., 25.}}
        Output: scalar
    }
]}

```

```

In[ ]:= p11 = ContourPlot[10^-2 + f[x, t] /. sol, {t, 0.2 tMin, tMax},
                    {x, -5, 2},
                    PlotRange -> {0, All}, PlotPoints -> 50, FrameLabel -> {"Time", "y"}];

```

(*Add boundary for where population is above a threshold*)

```

p11r = ContourPlot[10^-2 + f[x, t] /. sol,
                    {t, 0.2 tMin, tMax},
                    {x, -5, 2},
                    PlotRange -> {0, All}, PlotPoints -> 50, Contours -> {0.1},
                    ContourStyle -> {{Red, Thick}}, ContourShading -> None];

```

(*Location of peak of distribution*)

```

p13 = ListPlot[Table[{t, y /. FindMaximum[f[y, t] /. sol,
                    {y, -0.1 L, 0.1 L}][2]],
                    {t, 0.2 tMin, tMax, 0.1}], Joined -> True];

```


(*Combine all the parts of the plot together*)

```

Show[p11, p13, p11r]

```

Out[]:=



```

In[ ]:= (* Same plot, now in spatially fixed reference frame *)
(* Define f for fixed coordinate system *)
fFixed[x_, t_] = If[Abs[x - x0[t]] < L, 10^-2 + f[x - x0[t], t], 0] /. num;

(* Contour plot of f *)
pl1 = ContourPlot[fFixed[x, t] /. sol // Evaluate, {t, 0.2 tMin, tMax},
  {x, -5, 2},
  PlotRange -> {0, All}, PlotPoints -> 50, FrameLabel -> {"Time", "x"},
  PlotLegends -> BarLegend[Automatic, All, LegendLabel -> g[x]]];

(*Add boundary for where population is above a threshold*)
pl1r = ContourPlot[10^-2 + fFixed[x, t] /. sol // Evaluate,
  {t, 0.2 tMin, tMax},
  {x, -5, 2},
  PlotRange -> {0, All}, PlotPoints -> 50, Contours -> {0.1},
  ContourStyle -> {{Red, Thick}}, ContourShading -> None];

(*Location of peak of distribution*)
pl3 = ListPlot[Table[{t, (x0[t] /. num) + y /. FindMaximum[f[y, t] /. sol,
  {y, -0.1 L, 0.1 L}][[2]]},
  {t, 0.2 tMin, tMax, 0.1}],
  Joined -> True];

(*Combine all the parts of the plot together*)
Show[pl1, pl3, pl1r]

```

Out[]:=

